AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.2020
1. PRODUCT AND COMPANY ID	NTIFICATION	
Product name	: AeroShell Oil W 100	
Product code	: 001A0074	
Manufacturer or supplier's o	etails	
Supplier Telephone Telefax	 Shell Eastern Petroleum (Pte) Ltd (196000089G) The Metropolis Tower 1, 9 North Buona Vista Drive, #07-01 Singapore 138588 Singapore (+65) 62632975 (+65) 62632049 	
Emergency telephone number	: +65 6263 2975	
Email Contact for Safety Data Sheet	: If you have any enquiries about the please email lubricantSDS@shell.c	
Recommended use of the cl	emical and restrictions on use	
Recommended use	: Mineral lubricating oil for aircraft pist details consult the AeroShell Book o	

2. HAZARDS IDENTIFICATION

GHS Classification	
Based on available data this	substance / mixture does not meet the classification criteria.
GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	: Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

AeroShell Oil W 100

Version 1.8

Revision Date 04.08.2020

Print Date 26.10.2020

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous component	ts		
Chemical name	CAS-No.	Classification	Concentration (% w/w)
Alkylated phenol ester	125643-61-0	Aquatic Chronic4; H413	< 3

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.2020
Protection of first-aiders	: When administering first aid, ensu appropriate personal protective eq incident, injury and surroundings.	
Notes to physician	: Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: Foam, water spray or fog. Dry che dioxide, sand or earth may be use	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Hazardous combustion products n A complex mixture of airborne soli gases (smoke). Carbon monoxide may be evolved occurs. Unidentified organic and inorganic 	d and liquid particulates and I if incomplete combustion
Specific extinguishing methods	: Use extinguishing measures that a circumstances and the surrounding	
Special protective equipment for firefighters	: Proper protective equipment include gloves are to be worn; chemical re- large contact with spilled product is Breathing Apparatus must be worr a confined space. Select fire fighter relevant Standards (e.g. Europe:	esistant suit is indicated if s expected. Self-Contained n when approaching a fire in er's clothing approved to

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Avoid contact with skin and eyes.
a	: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	 Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020 Print Date 26.10.2020
	suitable material and dispose of properly.
Additional advice	 For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
7. HANDLING AND STORAGE	
General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	: Strong oxidising agents.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
Packaging material	: Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	PEL (long	5 mg/m3	SG OEL

AeroShell Oil W 100

Version 1.8	Revision Da	ate 04.08.2020	Print Da	te 26.10.2020
		term) (Mist)		
Oil mist, mineral	Not Assigned	PEL (short term) (Mist)	10 mg/m3	SG OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information:
	Define procedures for safe handling and maintenance of controls.
	Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
	Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
	Drain down system prior to equipment break-in or maintenance.
	Retain drain downs in sealed storage pending disposal or subsequent recycle.
	Always observe good personal hygiene measures, such as washing hands after handling the material and before eating,

AeroShell Oil W 100

sion 1.8	Revision Date 04.08.2020Print Date 26.10.202drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
Personal protective equip	ment
Protective measures	
Personal protective equipme PPE suppliers.	ent (PPE) should meet recommended national standards. Check wi
Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°((149°F)].
Hand protection Remarks	: Where hand contact with the product may occur the use of
	dives approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective han care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is no a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.2020
	protective eyewear is recommende	d.
Skin and body protection	 Skin protection is not ordinarily required work clothes. It is good practice to wear chemical 	
Thermal hazards	: Not applicable	
Environmental exposure co	ntrols	
General advice	 Take appropriate measures to fulfill relevant environmental protection le contamination of the environment b Section 6. If necessary, prevent un being discharged to waste water. W treated in a municipal or industrial w before discharge to surface water. Local guidelines on emission limits must be observed for the discharge vapour. 	egislation. Avoid by following advice given in dissolved material from /aste water should be waste water treatment plant for volatile substances

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at room temperature.
Colour	:	Various colours
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	<= -18 °C / <= -0.40 °FMethod: ASTM D97
Melting / freezing point		Data not available
Initial boiling point and boiling range	:	> 280 °C / 536 °Festimated value(s)
Flash point	:	>= 243 °C / >= 469 °F Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	:	> 1estimated value(s)
Relative density	:	0.887 (15.0 °C / 59.0 °F)

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.2020
Density	: 887 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6(based on information of	on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 204 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
	16.3 - 21.9 mm2/s (100 °C / 212 °F) Method: ASTM D445	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a	a static accumulator.

10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

AeroShell Oil W 100

Version 1.8 Basis for assessment	:	Revision Date 04.08.2020 Information given is based on data on the toxicology of similar products.Unler the data presented is representative of whole, rather than for individual compo	ss indicated otherwise, f the product as a
Information on likely routes of exposure	:	Skin and eye contact are the primary r although exposure may occur following	•
Acute toxicity			
Product:			
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classifica	tion criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the are not met.	elassification criteria
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classifica	tion criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.2020

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

•

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.202
	for this product. Information given is based on a and the ecotoxicology of similar Unless indicated otherwise, the representative of the product as individual component(s).(LL/EL nominal amount of product requ extract).	data presented is a whole, rather than for UL50 expressed as the
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg Practically non toxic: Based on available data, the cla	
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg Practically non toxic: Based on available data, the cla	
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg Practically non toxic: Based on available data, the cla	
Toxicity to fish (Chronic toxicity)	: Remarks: Data not available	
Toxicity to crustacean	: Remarks: Data not available	
(Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available	
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegrac inherently biodegradable, but co persist in the environment.	
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components bioaccumulate.	s with the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based o products)	n information on similar
lobility in soil		
Product:		
Mobility	: Remarks: Liquid under most en enters soil, it will adsorb to soil	

AeroShell Oil W 100

Version 1.8	Revision Date 04.08.2020	Print Date 26.10.2020
	Remarks: Floats on water.	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Does not have ozone depletion por ozone creation potential or global v is a mixture of non-volatile compor released to air in any significant qu conditions of use. Poorly soluble mixture., Causes ph organisms. Mineral oil does not cause chronic organisms at concentrations less th 	warming potential., Product nents, which will not be lantities under normal hysical fouling of aquatic toxicity to aquatic

13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks :	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

International Regulations

ADR Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

AeroShell Oil W 100

Version 1.8

Revision Date 04.08.2020

Print Date 26.10.2020

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Local Regulations

Workplace Safety and Health Act & Workplace Safety and Health (General Provision) Regulations	This product is not subject to the requirements in the Act/Regulations.
---	---

Fire Safety Act and Fire Safety (Petroleum &	This product is not subject to the requirements
Flammable Materials) Regulations	in the Act/Regulations.
·	·

Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations	This product is not subject to the requirements in the Act/Regulations.
--	---

Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances)	This product is not subject to control under this Act/ Regulation.
Regulations	

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other international regulations

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.

16. OTHER INFORMATION

Full text of H-Statements

H413 May cause long lasting harmful effects to aquatic life. **Full text of other abbreviations**

Aquatic Chronic Long-term (chronic) aquatic hazard

AeroShell Oil W 100

Version 1.8

Revision Date 04.08.2020

Print Date 26.10.2020

Abbreviations and Acronyms

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AeroShell Oil W 100

Version 1.8

Revision Date 04.08.2020 Print Date 26.10.2020

SG / EN